SL27-29-32W VENETIAN

MOTORISED BATTERY OPERATED WITH SOLAR PANEL

It's a battery-powered motorized system with the function of raising/lowering and tilting blinds.

Raising, lowering, or tilting the blinds is done using a touch control device that is magnetically attached to the window (or glass), or optionally, through a remote control. The battery can be recharged in two alternative ways: using a micro-USB charger or through an external solar panel, allowing for automatic and continuous charging.






The SL29C system comes standard with a 29mm-wide warm spacer bar in black (RAL9005). The SL27 and SL32 systems feature spacer bars of 27mm and 32mm respectively, made of extruded aluminum (also available in black).

This system is designed to be incredibly easy to install and can be used with all types of window frames, including those already in place. No wires or electrical contacts are necessary.

The battery module can be mounted on the window frame (along with the opening sash) or on the insulated glass unit (near the glazing bead).

CONTROL SYSTEM COLORS



SLAT COLORS

S102	S130	S155
S106	S142	S157
S125	S149	S156

In the W system, the battery module is equipped with a radio receiver, allowing you to activate individual blinds or groups of blinds using an optional remote control with 99 channels.



SL27W SL32W

POSSIBLE DIMENSIONS

MINIMUM DIMENSION		MAXIMUM DIMENSION	
WIDTH	HEIGHT	WIDTH	HEIGHT
320mm	300mm	3000mm	3000mm

THE MAXIMUM HEIGHT OF THE BLINDS DEPENDS ON THE WIDTH

Blinds with only the tilting function

WIDTH	MAXIMUM HEIGHT
320-389mm	3000mm

Blinds with the function of raising/lowering and tilting slats

WIDTH	MAXIMUM HEIGHT
390-419mm	1000mm *
420-449mm	1600mm *
450-599mm	2100mm *
600-3000mm	3000mm **

SL29W

POSSIBLE DIMENSIONS

MINIMUM DIMENSION		MAXIMUM DIMENSION	
WIDTH	HEIGHT	WIDTH	HEIGHT
340mm	300mm	3000mm	3000mm

THE MAXIMUM HEIGHT OF THE BLINDS DEPENDS ON THE WIDTH

Blinds with only the tilting function

WIDTH	MAXIMUM HEIGHT
340-399mm	3000mm

Blinds with the function of raising/lowering and tilting slats

WIDTH	MAXIMUM HEIGHT
400-430mm	1090mm *
431-460mm	1620mm *
461-490mm	2150mm *
491-520mm	2680mm *
521-3000mm	3000mm **

^{*} Up to H=3000 mm, blind supplied with tilt-only function and locked bottom rail



^{**} For areas from 4.01 m2 to 9m2, blind supplied with tilt-only function and completely raised